


### Product Features


- High precision instrument featuring 4 independent, non-dispersive infrared gas analyzer for both CO<sub>2</sub> and H<sub>2</sub>O (Differential Analyzer)
- CO<sub>2</sub> measurement range: Up to 10000 umol mol<sup>-1</sup>
- H<sub>2</sub>O measurement range: 0-75 mb
- Fast response and long term stability with built-in Auto Zero
- Fully compensated for changes in temperature, pressure and foreign gas broadening
- Large, full color 7" transfective LCD with optimized viewing angle (30°)
- Large numeric and graphical presentation of data
- Unlimited data storage (internal memory and USB flash drive)
- Analog and digital (USB) output
- Built-in sampling pump with mass flow controller
- Powerful, intuitive user interface and software
- On-line Help
- Remote display capability
- Internal 7.2V Li-Ion rechargeable battery (optional) for portability



### Numeric Display



### Graphical Display



### Applications


- Photosynthesis and respiration
- Plant physiology
- Soil CO<sub>2</sub> efflux
- Whole canopy assimilation
- Homemade chambers
- Global change & atmospheric studies
- FACE studies
- Forest & agricultural meteorology
- Air-sea surface exchange (pCO<sub>2</sub>)




## Powerful Software

Simple, intuitive and menu-driven software is designed into the system for system setup, operation, recording and data management. On-line help is available throughout the software to guide you every step of the way.

*Convenient, pluggable terminal block for analog signals.*



*Gas connections for direct connection to gas analyzers*



*For further information, please contact us at:*

**PP**  
**SYSTEMS**  
[www.ppsystems.com](http://www.ppsystems.com)

110 Haverhill Road · Suite 301  
Amesbury, MA 01913 U.S.A.  
TEL +1 978-834-0505  
FAX +1 978-834-0545  
EMAIL [sales@ppsystems.com](mailto:sales@ppsystems.com)  
URL [www.ppsystems.com](http://www.ppsystems.com)

Printed: December 2014  
Copyright © PP Systems 2014  
All rights reserved.

## Technical Specifications

<b>Analysis Method</b>	Non-dispersive infrared, configured as an absolute absorptiometer with micro-processor control of linearization. Four independent gas analyzers simultaneously measure absolute CO <sub>2</sub> and H <sub>2</sub> O for both reference and analysis gas streams. All measurements corrected for temperature and pressure.
<b>CO<sub>2</sub> Measurement Range</b>	0-10000 µmol mol <sup>-1</sup>
<b>CO<sub>2</sub> Precision</b>	<ul style="list-style-type: none"> <li>• 0.2 µmol mol<sup>-1</sup> at 300 µmol mol<sup>-1</sup></li> <li>• 0.5 µmol mol<sup>-1</sup> at 1750 µmol mol<sup>-1</sup></li> <li>• 3.0 µmol mol<sup>-1</sup> at 10000 µmol mol<sup>-1</sup></li> </ul>
<b>H<sub>2</sub>O Measurement Range</b>	0-75 mb
<b>H<sub>2</sub>O Precision</b>	<ul style="list-style-type: none"> <li>• 0.015 mb at 0 mb</li> <li>• 0.020 mb at 10 mb</li> <li>• 0.030 mb at 50 mb</li> </ul>
<b>Bandwidth (CO<sub>2</sub> and H<sub>2</sub>O)</b>	10 Hz (sampling rate). Sample data is averaged and output every 1.6 seconds.
<b>Pressure Range</b>	65-115 kPa
<b>Air Sampling</b>	User adjustable from 50-100 cc min <sup>-1</sup> using integral DC pump with mass flow controller.
<b>Auxiliary Port</b>	For connection to external sensors.
<b>Terminal Block</b>	Two 8 pin terminal blocks for simple connection to external devices.
<b>Digital Output</b>	<ul style="list-style-type: none"> <li>• USB-Mini b (Host)</li> <li>• 2 Ea. USB for use with external devices (Memory stick, USB Mouse, etc.).</li> </ul>
<b>Analog Output Channels</b>	4 Analog output channels available. Users can configure system to output CO <sub>2</sub> reference, CO <sub>2</sub> analysis, CO <sub>2</sub> differential, H <sub>2</sub> O reference, H <sub>2</sub> O analysis and H <sub>2</sub> O differential.
<b>Analog Output Range</b>	0-2.5V or 0-5V
<b>Analog Input Channels</b>	2 Analog input channels available for use with external sensors
<b>Analog Input Ranges</b>	0-1V or 0-5V
<b>Data Storage</b>	512 MB flash memory for programming and data storage. Unlimited data storage using USB thumb drives (memory sticks).
<b>Microprocessor Speed</b>	800 MHz
<b>Display</b>	7.0" WSVGA transfective, color LCD
<b>User Input</b>	27 key tactile keypad
<b>Power Supply (Optional)</b>	Internal, rechargeable 7.2V Li-ion battery providing up to 10 hours continuous use. Power supply/charger included.
<b>Operating Temperature Range</b>	0-50 °C, non-condensing. In dirty environments, external air filtration may be required.
<b>Enclosure</b>	Rugged, ergonomic, lightweight aluminum with polyurethane base.
<b>Dimensions</b>	28 cm (W) x 14.5 cm (D) x 24 cm (H)
<b>Weight</b>	3.8 kg (without battery). 4.3 kg (with optional battery).
<p>PP Systems is a registered trademark of PP Systems, Inc. PP Systems is continuously updating its products and reserves the right to amend product specifications without notice. All brand names are trademarks or registered trademarks of their respective owners.</p>	