

\* Optional collars are available for the CPY-4 Canopy Assimilation Chamber from PP Systems.



## **CPY-4 Canopy Assimilation Chamber**

The CPY-4 Canopy Assimilation Chamber is ideal for measurement of net canopy  $\mathrm{CO}_2$  flux on low-lying vegetation and fruit. Constructed of rugged polycarbonate, the interior of the transparent chamber includes a user-adjustable PAR (Photosynthetically Active Radiation) sensor and an air temperature sensor near the soil surface. An air mixing fan and custom manifold system ensures uniform circulation within the chamber. An aluminum ring provides a good seal on the soil surface or on collars.\* The Water Vapor Equilibrator comes standard.

 Dimensions
 145 mm (H) x 146 mm (Dia)
 Cable Length
 1.5 m

 Area
 167 cm²
 Weight
 0.9 kg

PAR SensorFully cosine correctedRange0 - 3000 μmol m-2 s-1

Accuracy  $\pm 5 \mu \text{mol m}^{-2} \text{ s}^{-1}$ Precision  $1 \mu \text{mol m}^{-2} \text{ s}^{-1}$  Temperature Sensor (Precision Thermistor)

Range 0-50 °C Accuracy  $\pm 0.5$  °C at 25°C

The CPY-4 Canopy Assimilation Chamber is compatible with the CIRAS-1 and CIRAS-2 Portable Photosynthesis Systems, and the EGM-1 through EGM-4 Portable  $CO_2$  Gas Analyzer models.

For further information, please contact us at:



110 Haverhill Road, Suite 301 Amesbury, MA 01913 U.S.A.

TEL +1 978-834-0505 FAX +1 978-834-0545 EMAIL sales@ppsystems.com

- PP Systems is a registered trademark of PP Systems, Inc.
- PP Systems is continuously updating its products and reserves the right to amend product specifications without notice.
- All brand names are trademarks of their respective owners.







