

# Soil Moisture & Soil Temperature



## Soil Moisture & Soil Temperature Probe

The **Stevens HydraProbe** is the most scientifically researched soil sensor available and is offered by PP Systems as an optional all-in-one, in-situ sensor for measurement of both soil moisture and soil temperature. This exceptionally rugged probe has completely sealed electronics making it fully immersible in water, and three strong, non-bending and non-corrosive stainless steel tines.



**Dimensions** 124 mm (L) x 26 mm (Dia)

**Cable Length** 7.62 m

### Soil Moisture Sensor

**Range** Dry - 100% of Saturation\*

\*Saturation of mineral soils depends on soil and typically occurs from 35 to 50 volumetric percent

### Soil Temperature Sensor

**Range** -10 °C to 55 °C

**Accuracy** ± 0.3 °C at 25 °C



*The Stevens HydraProbe is adapted for the CFLUX-1 Automated Soil CO<sub>2</sub> Flux System.*

For further information, please contact us at:



110 Haverhill Road, Suite 301  
Amesbury, MA 01913 U.S.A.  
TEL +1 978-834-0505  
FAX +1 978-834-0545  
EMAIL sales@ppsystems.com

- PP Systems is a registered trademark of PP Systems, Inc.
- PP Systems is continuously updating its products and reserves the right to amend product specifications without notice.
- All brand names are trademarks of their respective owners.



pp\_systems



company/pp-systems



ppsystems.intl



ppsystemsinc



ppsystemsinc